

Appln. No. 09/924,312
Amendment After Final Rejection dated May 28, 2003
Response to Office Action dated January 28, 2003

LISTING OF CLAIMS:

I-15. (Cancelled)

16. (Currently Amended) A method of manufacturing an ink cartridge,
comprising the steps of:
providing a container body, the container body including a material having a
wettability that increases when the material is exposed to ultraviolet radiation and having an ink
supply port shaped to receive an ink supply needle, having an inlet, formed in the container
body, for use in an ink jet recorder; ~~and, comprising the step of~~
treating at least a portion of the ink supply port inlet with ultraviolet radiation to
improve the wettability of the treated portion.

17. (Previously Amended) A method of manufacturing an ink cartridge for use in
an ink jet recorder, comprising the step of heating ink while it is being injected into the ink
cartridge, to a temperature of at least approximately 10 C° above the ambient temperature of the
ink, the ink being a liquid even when unheated.

18. (Previously Amended) A method of manufacturing an ink cartridge for use in
an ink jet recorder, comprising the step of heating ink while it is being injected into the ink
cartridge, to a temperature of between approximately 10 C° and 20 C° above the ambient
temperature of the ink, the ink being a liquid even when unheated.

Appln. No. 09/924,312

Amendment After Final Rejection dated May 28, 2003

Response to Office Action dated January 28, 2003

19. (Previously Amended) A method of manufacturing an ink cartridge for use in an ink jet recorder, comprising the step of heating ink while it is being injected into the ink cartridge, to a temperature of more than 20 C° above the ambient temperature of the ink, the ink being a liquid even when unheated.

20. (Currently Amended) A method of manufacturing an ink cartridge for use in an ink jet recorder, comprising the steps of:

providing a container body including a chamber for accommodating ink therein,
~~and an ink supply port communicating with the chamber, and an opening;~~

sealing the ink supply port;

bonding a cover to the opening of the container body;

injecting ink into the chamber;

~~depressurizing~~ reducing a pressure within the ink cartridge a first time to decrease an amount of any gas therein;

sealing a portion of the cover after the ~~first depressurizing~~ reducing step and then ~~depressurizing~~ reducing the pressure within the ink cartridge a second time to decrease further the amount of any gas therein; and

sealing the remainder of the cover after the second ~~depressurizing~~ reducing step.

21. (Previously Amended) The method of claim 20, wherein, prior to inserting the packing member, the container is positioned on the pallet such that the first wall faces upward away from the top of the pallet, and after inserting the packing member, resetting the container

Appln. No. 09/924,312
Amendment After Final Rejection dated May 28, 2003
Response to Office Action dated January 28, 2003

body on the pallet by turning the container body upside down such that the opening faces upward and the first wall faces the pallet.

22. (Original) The method of claim 20, comprising the step of affixing a filter to the ink supply port inlet.

23. (Currently Amended) The method of claim 20, wherein ~~the ink cartridge is depressurized~~ the pressure within the ink cartridge is reduced to approximately 200 mm Hg below atmospheric pressure during the second ~~depressurization~~ reducing step.

24. (Original) The method of claim 20, comprising the steps of inserting the container body into a bag having an opening and sealing the bag opening in a vacuum environment.

25. (Currently Amended) A method of manufacturing an ink cartridge for use in an ink jet recorder, comprising the steps of:

providing a container including a chamber for accommodating ink therein, and an ink supply port and an ink injection port, both communicating with the chamber;

sealing the ink supply port with a gas permeable and moisture impermeable film;

injecting ink into the chamber through the ink injection port;

~~depressurizing~~ reducing a pressure within the chamber to decrease an amount of any gas therein;

Appln. No. 09/924,312
Amendment After Final Rejection dated May 28, 2003
Response to Office Action dated January 28, 2003

sealing the ink injection port after ~~depressurizing~~the reducing of the pressure
within the chamber;

inserting the sealed container into a bag having an opening; and

sealing the opening of the bag in a ~~vacuum~~an environment having a reduced
pressure.

26. (Currently Amended) The method of claim 25, wherein the bag opening is
sealed in a vacuum environment within approximately 72 hours after the second
~~depressurization~~reducing step.

27. (Previously Amended) The method of claim 25, wherein, prior to inserting the
packing member, the container is positioned on the pallet such that the first wall faces upward
away from the top of the pallet, and after inserting the packing member, resetting the container
body on the pallet by turning the container body upside down such that the opening faces upward
and the first wall faces the pallet.

28. (Original) The method of claim 25, comprising the step of affixing a filter to
the ink supply port inlet.

29. (Cancelled)

30. (Currently Amended) A method of manufacturing an ink cartridge for use in
an ink jet recorder, comprising the steps of:

Appln. No. 09/924,312
Amendment After Final Rejection dated May 28, 2003
Response to Office Action dated January 28, 2003

providing a container including a chamber for accommodating ink therein, and an ink injection port communicating with the chamber;

injecting ink into the chamber through the ink injection port;

thereafter ~~depressurizing~~ reducing a pressure within the chamber to decrease an amount of any gas therein;

thereafter sealing the ink injection port; and

thereafter packing the container in a bag.

31. (Currently Amended) The method of claim 30, wherein the step of injecting ink is executed under a ~~depressurized~~ condition of reduced pressure.

32. (Currently Amended) The method of claim 30, wherein the step of packing the container is executed under a ~~depressurized~~ condition of reduced pressure.

33. (Previously New) The method of claim 30, wherein the container further comprises an ink supply port, and wherein prior to the step of injecting ink, the ink supply port is sealed.

34. (New) The method of claim 33, wherein the ink supply port is sealed with a gas permeable and moisture impermeable film.